

DS-2CE16H8T-IT3F
5 MP Ultra Low Light Fixed Bullet Camera



- 5 MP high performance bullet camera
- Strong night performance, capturing images in ultra-low light down to 0.003 lux
- Clear imaging even against strong back lighting due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- EXIR 2.0: advanced infrared technology with 60 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

Camera	
Image Sensor	5 megapixel progressive scan CMOS
Max. Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.003 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotate: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Focal Length & FOV	98° (2.8 mm), 78° (3.6 mm), 48° (6 mm), 37° (8 mm), 23° (12 mm)
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 60 m
Smart Supplement Light	Yes
Image	
Image Settings	Brightness, Mirror, Smart IR, Sharpness, AGC
Frame Rate	TVI: 5 MP@20 fps, 4 MP@25 fps/30 fps, 1080p@25 fps/30 fps AHD: 5 MP@20 fps, 4 MP@25 fps/30 fps CVI: 4 MP@25 fps/30 fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	≥130 dB
Image Enhancement	WDR, BLC
Privacy Mask	4 programmable privacy masks
Noise Reduction	3D DNR
White Balance	Auto/Manual
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS, 1 HD analog output
Event	
Motion Detection	4 programmable motion areas
General	
Power	12 VDC ± 25% *You are recommended to use one power adapter to supply the power for one camera. , Max. 5.8 W
Material	Metal
Dimension	81.9 mm × 86.7 mm × 217.9 mm (3.22" × 3.41" × 8.58")
Weight	Approx. 570 g (1.26 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67

▪ **Available Model**

DS-2CE16H8T-IT3F(2.8mm)

DS-2CE16H8T-IT3F(3.6mm)

DS-2CE16H8T-IT3F(6mm)

DS-2CE16H8T-IT3F(8mm)

DS-2CE16H8T-IT3F(12mm)

DS-2CE16H8T-IT3F(2.8mm)/Grey

▪ **Accessory**

▪ **Optional**

DS-1280ZJ-XS

Junction box



See Far, Go Further



www.hikvision.com
support@hikvision.com

