

## DS-PK1-LT-WE Wireless Keypad



- 868MHz two-way wireless communication
- LCD screen and LED to indicate system status
- System configuration through LCD screen
- Multiple operations like stay/away arm, disarm, silent alarm, output control
- One-Push fire alarm, panic alarm, and medical alarm
- Full touch key design with LED backlight
- Fully remote configurable through App



## ▪ Specification

| Hardware features          |                                                                                                           |
|----------------------------|-----------------------------------------------------------------------------------------------------------|
| Tag reader built in        | Supported                                                                                                 |
| Serial port                | 3                                                                                                         |
| Tamper-Proof               | Supported, front and rear                                                                                 |
| Buzzer                     | Supported                                                                                                 |
| Power switch               | Power on/off                                                                                              |
| Electrical characteristics |                                                                                                           |
| Battery type               | Four CR123 batteries                                                                                      |
| Operation humidity         | 10% to 90%                                                                                                |
| Operation temperature      | -10 °C to 55 °C                                                                                           |
| Battery life span          | Standby time more than two years                                                                          |
| Power consumption          | Quiescent current: 80 uA<br>Max current: 300 mA<br>Voltage: 3 V                                           |
| Wireless transmission      |                                                                                                           |
| RF frequency               | 868 MHz                                                                                                   |
| RF modulation              | 2GFSK                                                                                                     |
| RF distance                | 1200 m (open area)                                                                                        |
| Wireless technology        | Tri-X Wireless Technology                                                                                 |
| Display                    |                                                                                                           |
| Numeric key                | Number key: 0 to 9<br>Function key: *, #, Query, Away arm, Stay arm, Disarm, Output, Project, Right, Left |
| LED indicator              | Fault(orange), Enrollment/Signal (red/green), Arm(blue), Disarm(green), Alarm (red)                       |
| General                    |                                                                                                           |
| Installation method        | Wall mounting                                                                                             |
| Dimension(W×H×D)           | 174.63 mm × 109.62 mm × 25.25 mm                                                                          |
| Weight                     | With batteries: 348 g<br>Without batteries: 282 g                                                         |
| Color                      | White                                                                                                     |

## ▪ Available Model

DS-PK1-LT-WE

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com