

## DS-1006KI Serial Keyboard



- Full-featured RS-485 keyboard
- Supports various cameras, NVRs and DVRs
- Flexible 4-axis joystick
- Buttons can be used to perform powerful functions
- 128 × 64 screen displays all important information

## ▪ Specification

Interface	
USB Interface	USB 2.0 × 1
Serial Interface	RS-232 × 1, RS-485 × 1, RS-422 × 1
Wi-Fi	Not supported
Network Interface	Not supported
General	
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Net Weight	1.6 kg (3.53 lb.)
Dimensions (W × H × D)	348.2 mm × 169 mm × 123.2 mm (13.7 inch × 6.65 inch × 4.85 inch)
Power Consumption	≤ 4.7 W
Power Supply	12 VDC
Control Method	Serial control
Display	128 × 64 dot-matrix screen
Joystick	4-axis single button joystick
System	
Operating System Supported	Linux system
Certification	
Obtained Certification	CE-EMC/CE-LVD/ROHS/CB/UL/FCC-SDoC/IBIS

## ▪ Available Model

DS-1006KI

DS-1006KI(B)

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

