

## DS-XS6627-E/DW Free-standing Cabinet



- The Hikvision E-type server cabinet is compatible with 19 inch international standard floor standing glass door or perforated door cabinets. The cabinets are all made of high-quality cold-rolled sheet metal. Mainly used in data centers such as finance, securities, and data centers, it is specially designed for servers and can provide a high-performance and stable working environment for equipment in cabinets.

## ▪ Specification

Specifications	
Installation Method	Floor standing
Internal Space	27U
Static Load Capacity	500KG
Dimensions (W*D*H) mm	600*600*1385 (including casters)
Net Weight	41.05KG
Parameters	
Opening Percentage (Front Door)	78%
Opening Percentage (Rear Door)	78%
Front Door	1.2mm SPCC
Front and Rear Frame	0.8mm SPCC
Side Panel	0.8mm SPCC
Beam	1.2mm SPCC
Top Cover	0.8mm SPCC
Bottom panel	0.8mm SPCC
Vertical rail	1.2mm SPCC
Others	
Shelf	Optional: DS-XSPB06-E
Castor	4
Supporting leg	4
FAN	Optional: DS-XSFS06-E
PDU	Optional

## ▪ Available Model

DS-XS6627-E/DW

## ▪ Accessory

### ▪ Optional

DS-XPUK06-Y/KYL 6-ports 13A British standard PDU	DS-XPEUR08-Y/KYL 8-ports 16A European standard PDU	Cabinet Tray for E series Cabinet Tray for E series	Cabinet Fan for E series Cabinet Fan for E series
			

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

