

HYUNDAI NEXT GEN IP BULLET CAMERA PERFORMANCE LINE WITH IR OF 30M, 2 MP



PerformanceLine **IP67** **P2P**

ONVIF **EMP**

KEY FEATURES

- HYUNDAI NEXT GEN IP bullet camera Performance Line with IR of 30m, 2 MP
- H.265 / H.264 / MJPEG format
- 1/2.8" CMOS, 2MP
- Digital resolution of 1080P@25FPS
- Mechanical filter
- 0.028 lux
- 2.8 mm lens (114.8 °)
- OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, 3AXIS, 12V DC, PoE

FEATURES

- 1/2.8" CMOS sensor, 2 MP
- Up to 1080P (1920x1080) at 25 fps
- 2.8mm lens
- H.265, H.264, MJPEG video compression
- Dual stream
- Digital WDR, BLC, 3DDNR, 1 ROI
- IR illumination up to 30 meters
- IP67
- PoE supported

SPECS

- 1/2.8" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), etc.
- H.265 / H.264 / MJPEG compression format
- Main Stream: 1080P, 1.3MP, 720P (25 fps)
- Secondary stream: 640x480, 640x360, 320x240 (25 fps)
- Day/night mode with removable mechanical filter
- Infrared lighting: 30 meters
- 0.028 lux F2.0 color / 0 lux IR On
- 2.8mm lens with autofocus
- Viewing angle: 114.8 ° (H), 62 ° (V), 135.5 ° (D)
- OSD menu
- White balance adjustable from client software or web browser
- Automatic gain control
- Backlight Compensation: BLC
- Digital WDR
- 3D digital noise reduction
- 1 fixed ROI zone main stream
- Motion detection and privacy mask
- Adjust brightness, saturation, contrast and sharpness using client software or web browser
- Network interface: RJ45 (10 / 100M) autoadaptive
- Network protocols: TCP / IP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
- Compatible with ONVIF (Profile S), ISAPI
- Plug & Play connection with NVR NEXTGEN
- DDNS DEMES compatible
- Compatible with IE8 +, Chrome 3144, Firefox30-51, Safari 8+ browsers
- Power supply: 12V DC (± 25%)
- Consumption: 3.5W (PoE 4.5W)
- Supports 802.3af PoE, class 3
- Working temperature: 30 ° C ~ + 60 ° C
- Humidity: 95% (without condensation)
- IP67
- Metal and plastic case