

# DP-DE2108

## 8Ch HD Encoder



- Supports PTZ Control with UTC Protocol
- Supports 4 Audio input ports
- Supports Analog (CVBS), TVI, and AHD formats
- Supports Quadruple stream

### SPECIFICATIONS

Video	
Video Inputs	8 BNC
Max. Resolution	2560 x 1920
Network	
Video Compression	H.265, H.264
Max. Frame Rate	240ips@1080P, 144ips@3MP, 120ips@4MP, 80ips@5MP
Multi-video Streaming	Quadruple Streaming
Ethernet	RJ45 (10/100/1000 BASE-T)
Alarm and Event	
Trigger Event	Motion Detection, Tampering, Trip Zone, Video Loss
Event Notification	Remote S/W, Email (with Image)
Interface	
Audio In / Out	4 / -
Environmental	
Operating Temperature	0°C - 40°C (+32°F - +104°F)
Operating Humidity	0% - 90%
Electrical	
Power Source	12VDC, PoE IEEE 802.3af (Class 3)
Power Consumption	12V-, 0.8A, 10W PoE, IEEE 802.3af(Class 3), 10W
Approval	FCC, CE, KC
Mechanical	
Dimensions	200mm x 44mm x 165.2mm (7.9" x 1.7" x 6.5")
Weight	0.81kg (1.79lb)



### PRODUCT IMAGE



### DIMENSIONS

(Unit - mm)

