

DV-1304-A

4ch AI in the Box



- Simply connect to an IDIS NVR
- Supports Object Detection
- Supports Line Crossing
- Supports 4ch IP Camera
- Supports Intrusion
- Supports Face Detection
- Supports the most advanced IDIS Deep-Learning Analytics (IDLA)
- Supports Loitering
- Generating real-time event notifications with high accuracy

SPECIFICATIONS

Video	
Video Inputs	4 IP Channels
Supported Device	DirectIP NVR
VA Support	Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Network	
Video Compression	H.265, H.264
Network Connection	100M Ethernet x 1 (100Base-TX) with PD 100M Ethernet x 1 (100Base-TX) with PSE (PSE need Adaptor)
Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	0% - 90%
Electrical	
Power Input	48V-, PoE
Power Consumption	48V-, 0.8A, 38.4W PoE, IEEE 802.3at(Class 4), 25W DC OUTPUT : 48V-, 0.35A MAX
Approval	FCC, CE, KC
Mechanical	
Unit Dimensions (W x H x D)	200mm x 44mm x 157.6mm (7.9" x 1.7" x 6.2")
Unit Weight	0.88kg (1.94 lb)



PRODUCT IMAGE



DIMENSIONS

