

DV-1304

4ch AI in the Box



- Powered by the most advanced IDIS Deep-Learning Analytics (IDLA)
- Heatmap
- Generates real-time event notifications with high accuracy
- Rapid DirectIP plug-and-play installation
- People Counting and Occupancy Control
- Social Distancing Violation
- Live Occupancy Dashboard to maintain capacity limits
- Simply connect to an IDIS NVR
- Queue Monitoring
- Mask Rule Violation
- Dashboard Reporting for visitor flow, checkout traffic, and compliance adherence
- Supports 4-ch IP cameras

SPECIFICATIONS

| Video | |
|-----------------------------|-------------------------------------------------------------------------------------------------------------|
| Video Inputs | 4 IP Channels |
| Supported Device | DirectIP NVR |
| VA Support | People Counting, Occupancy Control Queue Monitoring Heatmap Social Distancing Violation Mask Rule Violation |
| Network | |
| Video Compression | H.265, H.264 |
| Network Connection | 100M Ethernet x 1 (100Base-TX) with PD 100M Ethernet x 1 (100Base-TX) with PSE (PSE need Adaptor) |
| Environmental | |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Operating Humidity | 0% - 90% |
| Electrical | |
| Power Input | 48V-, PoE |
| Power Consumption | 48V-, 0.8A, 38.4W PoE, IEEE 802.3at(Class 4), 25W DC OUTPUT : 48V-, 0.35A MAX |
| Approval | FCC, CE, KC |
| Mechanical | |
| Unit Dimensions (W x H x D) | 200mm x 44mm x 157.6mm (7.9" x 1.7" x 6.2") |
| Unit Weight | 0.88kg (1.94lb) |



PRODUCT IMAGE



DIMENSIONS

