

DC-T4233HRX

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Motorized Vari-focal lens (f= 2.8 - 12mm)
- micro SD/SDHC/SDXC
- Two-way audio
- Alarm in / out
- IK10 / IP67 supports
- Built-in heater
- PoE (IEEE 802.3af Class 3), 12V DC
- Day and night (ICR)
- True wide dynamic range (WDR)
- IR LED (Distance : 30m / 98.4ft)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	f = 2.8-12mm
Aperture	F 1.4-2.8
Iris Control	DC IRIS
Angular Field of View	Wide : 98°(H) 51°(V) 116°(D) Tele : 33°(H) 19°(V) 38°(D)
Min. Illumination	Color : 0.1 lux @ F1.4 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1~1/5, 1/7.5, 1/15)
Day and Night	IR cut filter with auto switch
IR Distance (LEDs)	30m / 98.4ft (6ea)
Image Setting	Configurable Exposure, White Balance, Sharpness
Digital Noise Reduction	Configurable 2DNR/3DNR
Backlight Compensation	On / Off
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	-
De-fog	On / Off
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - VBR / CBR H.264 - VBR / CBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF
Max. Frame Rate	30ips : 1920 x 1080(WDR)
Supported Resolution	1920 x 1080, 1280 x 720, 704 x 480, 640 x 360, 352 x 240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP Protocol, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, Upnp
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Audio Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (With Image)
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	PoE (IEEE 802.3af Class 3), DC12V
Power Consumption	12V=, 1.21A, 14.52W PoE, IEEE 802.3af(Class 3) , 11.1W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	Ø77m x 244.1mm (3" x 9.61")
Weight	0.84kg (1.85lb)

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

