

DH-2026PF

- Individual port data transmission to DirectIP NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Maximum per-device PoE delivery of 360W available for 1~24 RJ45 ports
- Central power control for greater network utility
- Supports 24 FE RJ45 ports and Uplink 2 GbE RJ45 / 2 GbE SFP combo slots



SPECIFICATIONS

SYSTEM	
System Memory	32MB SDRAM, 16MB Flash
Switching Capacity	8.8Gbps
CONNECTIVITY	
Copper Service Port	24 RJ45 Connectors (10/100BASE-T)
Copper Uplink Port	2 RJ45 / SFP combo (10/100/1000BASE-T/1000BASE-X)
Optical Uplink Port	-
PoE POWER	
Supported Standards	IEEE 802.3af-2003 / IEEE 802.3at-2009
PD Connection	Up to 24 IEEE 802.3af PDs or up to 12 IEEE 802.3at PDs
PSE Power	360W
GENERAL	
Dimensions (W x H x D)	430mm x 44mm x 235mm (13.4" x 1.7" x 9.25")
Weight	2.62Kg (5.77lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Input	100-240V~, 50/60Hz, 5.0-2.5A, 450W
Power Consumption	450W
Approvals	FCC, CE, KC, UL, CB

DIMENSIONS

(Unit - mm)

