

DH-2328PF

- Individual Port Data Transmission to DirectIP™ NVR
- PoE (IEEE 802.3af, IEEE 802.3at) Compliant
- Maximum Per-Device PoE Delivery of 380W Available for 1~24 RJ45 Ports
- Central Power Control for Greater Network Utility
- Supports 24 GbE RJ45 Ports and Uplink 4 GbE SFP Slots



SPECIFICATIONS

SYSTEM	
System Memory	512MB SDRAM, 256MB Flash
Switching Capacity	56Gbps
CONNECTIVITY	
Copper Service Port	24 RJ45 Connectors (10/100/1000BASE-T)
Copper Uplink Port	-
Optical Uplink Port	4 SFP Slot (1000BASE-X)
PoE POWER	
Supported Standards	IEEE 802.3af-2003 / IEEE 802.3at-2009
PD Connection	Up to 24 IEEE 802.3af PDs or Up to 12 IEEE 802.3at PDs
PSE Power	380W
GENERAL	
Dimensions (W x H x D)	440mm x 42.8mm x 268mm (17.3" x 1.7" x 10.6")
Weight	4.28kg (9.42lb)
Operation Temperature	0°C to +50°C (-32°F~ 122°F)
Power Input	100-240V~, 50/60Hz, 5.5-2.5A
Power Consumption	460W
Approvals	FCC, CE, KC

DIMENSIONS

(Unit - mm)

