

DS-1NP6UECO

CAT6, U/UTP, 24AWG, CU



- Stable electrical performance, compliant with TIA-568.2-D,ISO/IEC 11801.
- Bare Copper conductor with less resistance, and better electrical properties and transmission performance.
- Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the project.
- Gold plated plug, less resistance, less Insertion loss.
- Excellent performance in the Fluke 90-meter permanent link test.
- Excellent performance in the Fluke 100-meter channel test.
- Compliant with RoHS 2.0.
- Suitable for 10BASE-T, 100BASE-TX Fast Ethernet, and 1000BASE-T /1000BASE-TX (Gigabit Ethernet).

▪ Specification
















Patch cord	
Category	Cat 6
length	0.5,1,2,3,5,10m
Operating Voltage	57V
Patch cord	
Conductor Material	Bare Copper (99.95%)
Conductor Diameter	7*0.2mm 24AWG
Patch cord	
Insulation Material	HDPE
Patch cord	
Sheath Material	PVC
Sheath Thickness	0.50 ± 0.05mm
Sheath Diameter	5.8±0.20 mm
Sheath Color	Orange/Gray
Patch cord	
Plug Material	PC UL94V-0
Gold Plating	30u inch
Patch cord	
Impedance	100±15 Ω
DC Resistance	≤ 9.4 Ω/100 m

▪ Available Model

DS-1NP6UECO 橙色 0.5米
 DS-1NP6UECO 灰色 0.5米
 DS-1NP6UECO 橙色 1米
 DS-1NP6UECO 灰色 1米
 DS-1NP6UECO 橙色 2米
 DS-1NP6UECO 灰色 2米
 DS-1NP6UECO 橙色 3米
 DS-1NP6UECO 灰色 3米
 DS-1NP6UECO 橙色 5米
 DS-1NP6UECO 灰色 5米
 DS-1NP6UECO 橙色 10米
 DS-1NP6UECO 灰色 10米

▪ Accessory

▪ Optional

DS-D4012CS-1F P1.2 640*480 Indoor LED	DS-D4015CS-1F P1.5 640*480 Indoor LED	DS-D4018CS-1F P1.8 640*480 Indoor LED	DS-D4020CS-1F P2.0 640*480 Indoor LED	DS-D4025CS-1F P2.5 640*480 Indoor LED
				
DS-D4009BW-2FC DS-D4009BW-2FC 600*337.5/mm (O-STD)	DS-D4012BW-2FC DS-D4012BW-2FC 600*337.5/mm (O-STD)	DS-D4015BW-2FC DS-D4015BW-2FC 600*337.5/mm (O-STD)	DS-D4012CW-2F DS-D4012CW-2F 600*337.5/mm (O-STD)	DS-D4015CW-2F DS-D4015CW-2F 600*337.5/mm (O-STD)
				
DS-D4018CW-2F DS-D4018CW-2F 600*337.5/mm (O-STD)	DS-D4012CW-2FQ DS-D4012CW-2FQ 600*337.5/mm箱体 五代 (海外仓标配)	DS-D4015CW-2FQ DS-D4015CW-2FQ 600*337.5/mm箱体 五代 (海外仓标配)	DS-D4018CW-2FQ DS-D4018CW-2FQ 600*337.5/mm箱体 五代 (海外仓标配)	DS-D4012CW-2FQ/ M DS-D4012CW-2FQ/ M(Module) 箱体灯 板备件
				
DS-D4015CW-2FQ/ M DS-D4015CW-2FQ/ M(Module) 箱体灯 板备件	DS-D4018CW-2FQ/ M DS-D4018CW-2FQ/ M(Module) 箱体灯 板备件	DS-D4012NW-2F DS-D4012NW-2F 600*337.5/mm箱体 五代 (海外仓标配)	DS-D4015NW-2F DS-D4015NW-2F 600*337.5/mm箱体 五代 (海外仓标配)	



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

