

DS-D4239FO-CLF/A module



- Support front and rear maintenance
- Using aluminum chassis with good heat dissipation, workable under 60 °C
- All series aluminum profile cabinets support IP67(F)/IP66(R)
- Apply unique technology, maximally saving 30% energy
- Various cabinet sizes, applying to diverse scenes
- The cabinets support customized 45° corner cut to realize 90° right-angle splicing

▪ Specification

Cabinet	
Pixel Configuration	1R1G1B
Pixel Pitch Category	P3.91
Pixel Pitch	3.91mm
Lamp Dimensions	1921
Modules Component	Aluminum Shell
Dimensions (W × H × D)	250 mm × 500 mm
Resolution	64*128
Pixel Density	65536dots/m ²
Cabinet Material	Aluminum Profile
Key Material	
Driver IC	SM16169
Display	
White Balance Brightness	4500
Color Temperature	3000K-10000K
Viewing Angle	160° (H) /80° (V)
Contrast Ratio	5000:1
Color Uniformity	≥95%
Brightness Uniformity	≥95%
Processing Performance	
Driving Method	Constant Current
Frame Frequency	50/60HZ
Refresh Rate	3840
Grey Level	14bit
Display Color	DCI-P3 > 85%
Power	
Power Supply	110-220
Max. Consumption	650
Average Consumption	210
Working Environment	
Working Temperature	-40~+60°C
Working Humidity	10% to 95% RH (non-condensing)
Storage Humidity	10% to 95% RH (non-condensing)
Storage Temperature	-40~+80°C
General	
Gross Weight	1.6kg
Package Dimension (W × H × D)	550×300×70
Lifespan	100000 Hours

▪ Available Model

DS-D4239FO-M

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

