



KEY FEATURES

- 16 ch HYUNDAI NEXTGEN IP NVR
- H.265/H.265+/ H.264/H.264+/MPEG4
- Synchronous playback of 16 channels
- Display up to 8MP
- Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc
- Recording up to 160 Mbps
- HDMI 4K and VGA 1080P output
- 2 way audio
- Supports 1 SATA HDD
- RJ45 Gigabit Compatible Onvif, P2P, DDNS

FEATURES

- 16 IP inputs
- Video format H.265 + / H.265 / H.264 + / H.264
- Resolution recording up to 8MP (3840x2160)
- HDMI (4K) and VGA (1080P) video output
- 2 SATA ports
- Ethernet Gigabit port
- 16 PoE ports

SPECS

- The H.265 + compression format improves coding efficiency by up to 70% and reduces the costs of storing video data
- 16 IP camera inputs
- Incoming bandwidth: 160 Mbps
- Outgoing Bandwidth: 80 Mbps
- 1 HDMI 4K output + 1 VGA 1080P output
- Bidirectional audio: 1 RCA input / 1 RCA output
- Recording resolution: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, etc.
- Live display up to 8MP
- Allows instant playback of assigned channel during multichannel display mode
- Simultaneous playback of 16 channels, 1 channel 8MP
- Connectable to thirdparty IP cameras
- Centralized management of IP cameras, including configuration, import / export information, realtime information display, bi-directional audio, update, etc.
- Supports VCA (Video Content Analytics) alarm detection
- Intelligent search for motion detection recordings
- Storage: 2 SATA ports for up to 2 HDDs up to 6TB (HDD not included)
- 1 RJ45 (10/100 / 1000M) autoadaptive port
- Protocols: TCP / IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
- ONVIF compatible
- Remote access through iPhone / iPad devices, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P in the cloud, DDNS DEMES, Push and zero channel
- Plug & Play connection with NEXTGEN IP cameras
- Connections: 2 USB 2.0
- Power: 100V ~ 220V AC
- 8 PoE + 802.3af / at ports
- NVR consumption: ≤15W (without hard drives or PoE)
- PoE consumption: ≤150W
- Operating temperature: 10 ° C ~ + 55 ° C
- Relative humidity: 10 ~ 90%
- Dimensions: 385 (W) x 315 (H) x 52 mm