

4 CHANNEL 5 IN 1 ZVR HDCVI/HDTV/ AHD/ CVBS + 1 IP CHANNEL

## KEY FEATURES

- 4 channel 5 in 1 ZVR HDCVI/HDTV/ AHD/ CVBS + 1 IP channel
- H.265+/H265/H.264+/H264
- 2 way audio
- 4 channel playback at 1080P
- Recording: 4M-N, 3MP (channel1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps)
- BNC output at D1/4CIF
- HDMI and VGA output at 1080P
- 1 HDD SATA
- Onvif, P2P, DDNS
- 2 USB, 1 RS485
- 12V DC



**H.265+ P2P Onvif HDCVI™**  
**HDTV AHD CVBS**

## RELATED PRODUCTS



HYU-370-1TB



- 4 channel 5 in 1 ZVR, H.265+/H265/H.264+/H.264
  - 5 technologies: IP cameras, HDCVI, HDTV, AHD and CVBS
  - H.265+ compression format improves storage and coding up to 70%
  - 4 BNC inputs (coaxitron supported):
  - HDCVI: 1080P/720P (telemetry control via coaxial cable of HDCVI cameras)
  - HDTV: 4MN / 3MP (1 channel) / 1080P / 720P (only v3.0 cameras, not compatible with v1.0)
  - AHD: 1080P/720P
  - CVBS: 960H
  - 1 IP input up to 4MP
  - VGA and HDMI output up to 1920x1080
  - BNC auxiliary interface up to 704x576
  - 2 way audio: 1 RCA in / 1 RCA out
  - Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
  - Recording resolution: 4M-N, 3MP (channel 1, only TVI), 4MP (IP only), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
  - **Stream 1 on 4M-N/3MP mode:**
  - Stream at 4MN/3MP: 4M-N, 3MP (15 fps)
  - Stream 1 on 1080P mode:
  - Stream at 1080P: 1080P, 720P (15 fps), 960H, D1/4CIF, VGA, CIF (25/30 fps)
  - Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
  - Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
  - 4 channel simultaneous playback at 1080p
  - Multi-camera inverse playback
  - Local playback speed up to x 256 (forward and backward)
  - 1 HDD SATA internal capacity up to 6TB (not included)
  - Supports hard disk quota mode; allows assigning different capacities to different channels
  - Graphical user interface (GUI) and one-button recording support (Wizard)
  - Video quality diagnostic manual
  - Search and reproduction by tags
  - Locking and unlocking log files
  - Ethernet network interface RJ45 (10/100M) auto-adaptive
  - Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
  - Compatible with ONVIF
  - Remote access up to 128 users
  - Remote access via iPhone/iPad, Android
  - Multi browser compatibility: Chrome, Firefox, Safari, IE
  - P2P cloud, DDNS DEMES, Push and channel zero
  - Connections: 2 USB 2.0, 1 RS485 half-duplex
  - Power supply: 12V DC
  - Consumption: ≤6W
  - Working temperature: -10°C ~ +55°C
- RH: 10~90%
  - Dimensions: 315 x 242 x 45 mm (desktop)
  - Weight: ≤1,16 kg