



KEY FEATURES

- 4 channel 5 in 1 ZVR
HDCVI/HDTV/AHD/CVBS + 1 IP channels
- H.265+/H265/H.264+/H264
- 2 way audio
- 4 channel playback 1080P
- Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps)
- BNC output at D1/4CIF
- HDMI and VGA at 1080P
- 1 HDD SATA capacity
- RJ45 Gigabit
- Onvif, P2P, DDNS

RELATED PRODUCTS



4 CHANNEL 5 IN 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP CHANNELS

- 4 channel 5 in 1 ZVR, H.265+/H265/H.264+/H.264
- 5 technologies: IP, HDCVI, HDTV, AHD and CVBS
- PoC (Power Over Coaxial) for HDTV compatible cameras (up to 200 meters)
- TVI mode: 3.0 version (not compatible with v1.0)
- H.265+ compression format (reduction of 70% coding efficiency and video storage)
- 4 BNC input (coaxitron supported): HDCVI: 1080P/720P (telemetry control via HDCVI coaxial cable) HDTV: 3MP (channels 1) / 1080P / 720P (only on v3.0 cameras, not compatible with v1.0) AHD: 1080P/720P CVBS : 960H
- 1 IP inputs up to 4MP
- HDMI & VGA output 1920x1080
- BNC auxiliary output up to 704x576
- 2 way audio: 1 RCA in / 1 RCA out
- Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
- Recording resolution: 3MP (channels 1, only TVI), 4MP (only IP), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
- Stream 1 on 3MP mode: Stream at 3MP: 3MP (15 fps)
- Stream 1 on 1080P mode: Stream at 1080P: 1080P, 720P (15 fps), 960H, D1/4CIF, VGA, CIF (25/30 fps) Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream 1 on 1080N mode:
 - 3MP (15 fps), 1080N, 720P lite, 960H, D1/4CIF, VGA, CIF (25/30 fps)
 - Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
- 4 channel simultaneous playback 1080P
- Multicamera inverted playback
- Up to x256 playback speed (forward and backward)
- 1 HDD SATA up to 6TB (not included)
- Soporta modo de cuota de disco duro; permite asignar capacidades diferentes a canales diferentes
- GUI and one touch recording (Wizard)
- Diagnosys manual of video quality
- Search and playback by tags
- Log files locking and unlocking
- Network interface: Ethernet RJ45 (10/100/1000M) autoadaptive
- Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 128 users
- Remote access via iPhone/iPad, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P, DDNS DEMES, Push and zero channel
- Connection: 2 USB 2.0, 1 RS485 halfduplex
- Power supply: 48V DC
- Consumption: ≤40W
- Working temperature: 10°C ~ +55°C
- RH: 10~90%
- Dimensions: 315 x 242 x 45 mm (desktop)
- Weight: ≤1,16 kg