

8 CHANNEL 5 IN 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP CHANNEL



KEY FEATURES

- 8 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channel
- H.265+/H265/H.264+/H264
- 2 way audio
- 8 channel playback at 1080P
- Recording: 3MP (channel 1 and 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps)
- BNC output at D1/4CIF
- HDMI and VGA output at 1080P
- 2 HDD SATA capacity
- Onvif, P2P, DDNS
- 2 USB, 1 RS485
- DC48V
- Compatible with PoC cameras

PoC Power over Coax IP46 P2P ONVIF HDCVI™
HDTVI AHD CVBS

RELATED PRODUCTS





- 8 channel 5 in 1 ZVR, H.265+/H265/H.264+/H.264
- 5 technologies: IP, HDCVI, HDTVI, AHD and CVBS
- Power supply PoC (Power Over Coaxial) for compatible HD-TV cameras (up to 200 meters)
- TVI mode: 3.0 version (not compatible with v1.0)
- H.265+ compression format (reduction of 70% coding efficiency and video storage)
- 8 BNC inputs (coaxitron supported):
- HDCVI: 1080P/720P (telemetry control by coaxial cable of HDCVI cameras)
- HDTVI: 3MP (canales 1 y 2) / 1080P / 720P (only on v3.0 cameras, not compatible with v1.0)
- AHD: 1080P/720P
- CVBS: 960H
- 2 IP inputs up to 4MP
- VGA and HDMI output up to 1920x1080
- BNC auxiliary output up to 704x576
- 2 way audio: 1 RCA in / 1 RCA out
- Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
- Recording resolution: 3MP (channel 1 and 2, only TVI), 4MP (only IP), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
- Stream 1 on 3MP mode:
- Stream at 3MP: 3MP (15 fps)
- Stream 1 on 1080P mode:
- Stream at 1080P: 1080P, 720P (15 fps), 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream 1 on 1080N mode:
- 3MP (15 fps), 1080N, 720P lite, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
- 8 channel simultaneous playback 1080P
- Multi-camera inverse playback
- Local playback speed up to x256 (forward and backward)
- 2 HDD SATA internal capacity up to 6TB (not included)
- Supports hard disk quota mode; allows assigning different capacities to different channels
- Graphical user interface (GUI) and one-button recording support (Wizard)
- Video quality diagnostic manual
- Playback and search by tag
- Lock and unlock log files
- Network interface: Ethernet RJ45 (10/100M) auto-adaptive
- Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 128 usuarios
- Remote access via iPhone/iPad, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P cloud, DDNS DEMES, Push and channel zero
- Connections: 2 USB 2.0, 1 RS485 half-duplex
- Power supply: 48V DC
- Consumption: ≤60W
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 380 x 320 x 48 mm (desktop)
- Weight: ≤1,78 kg