

IP BULLET CAMERA WITH IR OF 30M, FOR OUTDOORS, 2 MP



PerformanceLine **IP67** **P2P**



KEY FEATURES

- IP bullet camera with IR of 30m, for outdoors, 2 MP
- H.265+, H.265, H.264+, H.264
- 1/2,8" CMOS, 2MP
- Digital resolution 1080P, 1,3MP, 720P, etc
- Mechanical filter
- 0,01 lux
- 2,8 mm (103°) fixed lens
- OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI
- IP67
- 3AXIS

- 1/2,8" CMOS sensor, 2 MP- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.- H.265+, H.265, H.264+, H.264- Stream 1: 1080P, 1,3MP, 720P (25/30 fps)- Stream 2: 704x576 (25 fps), 704x480 (30 fps), 640x480, (25/30 fps), 352x288 (25 fps), 352x240 (30 fps), 320x240 (25/30 fps)- Day/night mode with removable mechanical filter- IR illumination: 30 meters- Minimum illumination: 0,01 lux F1.2 color / 0 lux IR On- 2,8 mm fixed lens (103°)- OSD menu, AGC, BLC, digital WDR, 3D-DNR- 1 fixed ROI zone- Motion detection and privacy mask- Bright adjustment, saturation, contrast, sharpness, mirror- Network interface: RJ45 (10/100 Base-T) - Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour- Compatible with ONVIF (Profile S, G), PSIA, CGI, ISAPI- Plug&Play with NVR NEXTGEN- Compatible with DDNS DEMES- Power supply: 12V CC /5W (Max 6,5W PoE)- PoE 802.3af supported- Working temperature -30°C ~ +60°C- RH: 95%- IP67- PVC and metal case- Dimensions: 69,1 x 66 x 172,7 mm- Weight: 500 g- 3AXIS bracket- Power supply is not included