

4 CHANNEL 5 IN 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP CHANNELS

KEY FEATURES

- 4 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channels
- H.265 Pro+, H265 Pro, H.265, H.264+, H.264
- 2 way audio
- 4 channel simultaneous playback
- Recording: 6MP (only IP), 4M-N, 3MP (channel 1, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps)
- HDMI and VGA simultaneous output at 1080P
- BNC output at D1/4CIF
- 1 HDD SATA
- Onvif, P2P, DDNS
- 2 USB, 1 RS485
- 12V DC



H.265 **P2P** **ONVIF** **HDCVI™**
HDTVI **AHD** **CVBS** **aisense**



- Aisense series
- Aisense is able to differentiate, with great precision, a human body and a vehicle on a large number of objects. Not only can detect human and vehicle intrusion, it can also filter out false alarms that could have been triggered by moving objects that do not threaten.

SPECS

- 4 channel 5 in 1 ZVR H.265 Pro+/H265 Pro/H.265/H.264+/H.264
- 5 technology: IP, HDCVI, HDTV, AHD and CVBS
- H.265 Pro+ / H.265 Pro
- 4 BNC input (coaxitron supported):
- HDCVI: 1080P / 720P
- HDTV: 4MN / 3MP (canal 1) / 1080P / 720P
- AHD: 4MN / 1080P/720P
- CVBS: 960H
- 2 IP inputs up to 6MP (Up to 6 IPC in NVR mode without analogue HD cameras)
- VGA and HDMI simultaneous output up to 1920x1080
- BNC video output
- 2 way audio: 1 RCA in / 1 RCA out
- Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF
- Recording resolution: 6MP (only IP), 4M-N, 3MP (channel 1, TVI/AHD), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF
- **Stream 1 on 4M-N/3MP:**
- Stream at 4MN/3MP: 4M-N, 3MP (15 fps)
- **Stream 1 on 1080P:**
- Stream at 1080P: 1080P (15 fps), 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
- Simultaneous playback: 4 channel
- Maximum output bandwidth of 72 Mbps
- 1 HDD SATA internal capacity up to 10TB (not included)
- Supports hard disk quota mode; allows you to assign different capabilities to different channels
- Graphical user interface (GUI) and one-key recording start support (Wizard)
- Manual video quality diagnosis (VCA)
- Smart search for more efficient reproduction
- Supports third-party cloud storage (Dropbox, Google Drive, Microsoft OneDrive)
- Up to 2 channels of deep analysis based on learning: recognition of the human body or vehicles in the detection of behaviors to reduce false alarms
- Ethernet RJ45 (10/100M) auto-adaptive
- Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 32 users
- Remote access via iPhone/iPad, Android

- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P cloud, DDNS DEMES, Push and channel zero
- Connection: 2 USB 2.0, 1 RS485 half-duplex
- Power supply: 12V DC
- Consumption: ≤10W
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 315 x 242 x 45 mm (desktop)
- Weight: ≤1,16 kg