

DS-PEA22 Series Box Panic Alarm Station

DS-PEA22 series box panic alarm station is designed with 2 MP HD camera and dual network ports. It supports scheduled turning on/off the alarm lamp, two-way audio. It helps to realize immediate alarm and aid, which can be mainly applied to school, square, tourist attraction, hospital, supermarket gate, market, station, parking lot, etc.



Key Features

- Supports network adaptive and video and audio adaptive to realize low latency
- H.264, H.264 SVC and H.265 video compression standard, and G.711U and G.726 audio compression standard
- Wide dynamic range (WDR) and high light compensation (HLC)
- Multiple communication protocols: TCP/IP, SNMP, HIK-SIP, RTSP
- Video collection and all-day monitoring with 2 MP HD IR camera
- Supports ISUP and Hik-Connect service for public network transmission
- Two-way audio function with up to 5 m communication distance
- Build-in high sensitive microphone
- Audio extension with 3.5 mm standard audio interface
- Build-in loudspeaker and pickup with cracking voice prevention
- External audible and visual alarm
- Dual network ports

Available Models

DS-PEA22-B(B)



Specifications

Model	DS-PEA22 Series Box Panic Alarm Station	
Build-in camera parameters	Camera	2 MP HD IR Camera, IR Distance \geq 10 m
	FOV	Horizontal: 128°, Vertical: 75°, Diagonal: 147°
	Day & night	IR Cut Filter
	Video compression standard	H.264, H.264 SVC, H.265
	Resolution	1920*1080@25fps
Audio parameters	Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
	Audio output	1-ch 3 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output
	Audio compression standard	G.711 U/64Kbps, G.726 /16Kbps
	Audio quality	Noise Suppression and Echo Cancellation
Network parameters	Network protocol	TCP/IP, RTSP, SNMP, and HIK-SIP
	Ethernet	10 M/100 M Self-adaptive Ethernet Port
	Public network transmission	ISUP 2.0/ Hik-Connect /Standard SIP
	Network encryption	Supports User Lock-in and Password Security Prompt
Alarm	One-touch alarm	Supported
	Tampering Alarm	Supported
Device interfaces	Ethernet port	2 RJ45 10 M/100 M Self-adaptive Ethernet Port
	IO Input	2
	IO Output	2
	Alarm lamp	Supported, Light Can be Configured Separately
	Siren	Supported, Sound Can be Configured Separately
	SD Card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G
	PSTN	1-ch
General	Power supply	100-240 VAC
	Power consumption	\leq 24W
	Working temperature	-40 °C to +60 °C (-40 °F to 140 °F)
	Working humidity	10% to 90%
	Installation	Hold Hoop and Wall Mounting
	Dimensions	516.5 mm \times 327.7 mm \times 125 mm (20.33" \times 12.90" \times 4.92")

