

# TVI2.0 tester

## 1. Image



## **2. Product list**

1. 12.6V charger(EU/US standard) x 1
2. BNC cable x 1
3. DC-DC cable x 1
4. Combined cable x 1
5. Adaptor x 2
6. User manual x 1

## **3. Key features**

1. ABS+PC enclosure
2. 7" LCD screen, up to 800\*480 resolution
3. 3-battery(2600MA) with 6A protective board
4. TVI2.0 mainboard
5. VGA/HDMI input, up to 1920\*1080 resolution

## **4. Video input**

1. TVI2.0 up to 720P@25/30/50/60fps and 1080P@25/30fps
2. Up the Coax function(HIKVISION-C protocol)
3. CVBS signal with PAL/NTSC/SECAM system
4. VGA video input
5. HDMI1.0

## **5. Power supply**

1. Max.12.6V with 3-battery cascade
2. 11.1V-12.6V power supply for camera with DC-DC or USB combined cable, maximum 2A output
3. Special charger for 12.6V battery, input voltage is between 110V-230V, output voltage is 12.6V/1A. Optional US/ EU standard

## **6. Power Consumption**

Max. 2.9W when TVI OFF

Max. 4.8W when TVI ON

## **7. Dimension**

Tester only: 205MM\*155MM\*38MM

Tester with package: 28.5CM\*18.5CM\*7CM

Carton: 36.5CM\*30CM\*40CM(include 10 tester package)