

IP camera Tester

IPC-9800

IPS 7 inch TFT-LCD test monitor with capacitive touch screen / ONVIF IP camera test, 2592*1520 /IP CVBS 1080P camera / WIFI /12V 2A Power output / 5V 2A power bank / DC48V PoE power supply /HDMI output/ IP camera viewer /PTZ control /Ping test/ UTP cable test /IP discovery, Auto -search IP camera address / Rapid ONVIF, Auto-login and display the camera image, activate Hikvision camera quickly. Support more than 80 IP camera brands test (Hikvision, Dahua, Honeywell, Samsung etc)

7 inch tester monitor is designed for maintenance and installation of IP CVBS cameras as well as other security equipment. It's 1280 x 800 resolution enables it to display images from network HD cameras and analog cameras in top quality, it supports ONVIF PTZ and analog PTZ control. A combination of touch screen and push buttons make the IP camera tester very user friendly. In addition the tester is also a great tool for Ethernet networks and cabling systems. It can test PoE voltage and is capable of IP address searching.

Other functions built in WIFI, UTP cable tester, 12V 2A power output for camera, DC48V PoE power supply, 5V 2A power output, HDMI output, Audio input and output, Network bandwidth testing, OSD menu rotates in 180 angle, OSD menu can be rotated in 180 angle by manual setting. The meters portability, user-friendly design and multi-function capability make it an essential tool for installers and technicians, greatly improving work efficiency and simplifying installations and system maintenance.

Application

- CCTV system installation and maintenance
- Network cabling project installation and maintenance
- Dome camera IP camera testing
- Video transmission channel testing
- PTZ controller

Features

- 7 inch IPS TFT-LCD test monitor with capacitive touch screen, 1280*800 resolution NEW
- Brightness/contrast/color saturation adjustment
- Built in Wi-Fi can receive images from wireless cameras,
- ONVIF IP camera test, support 2592*1520
- Test H.264/MPEG4/MJPEG IP cameras
- Video image magnification enables detailed viewing
- HDMI signal output, support 1080p
- Analog camera image display, auto adapts and display NTSC or PAL video formats
- Customized IP cameras (with more than 80 brand camera, such as DAHUA, Haikang, KEDA, Samsung, HIKVISION and TIANDY camera)
- IP discovery, auto scan the IP camera address
- Rapid ONVIF, search camera quickly, auto log in and display image from the camera, activate Hikvision camera.
- Hik test tool app is design for activating and debugging Hikvision camera can auto-identify inactivated hikvision camera, also can display image from the Hikvision camera.
- DH test tool app is design for Dahua Camera image test, support modify IP, user name and password etc parameters.
- DC48V PoE power output, supplies temporary power for PoE cameras
- Supports RS232/RS485, Rate 600 - 115,200bps adjustable



16. Snapshot and save images as JPG files in an SD card, video record and playback
17. Support mobile client of the IP camera
18. Display real resolution of the IP camera images
19. PTZ controller ,Photograph, Video record, Record playback
20. Color bar generator, analog video color bar and testing image output
21. POE voltage test, PING test ,IP address scan, port flashing etc
22. 12V /2A power output
23. 5V 2A power output, as the power bank
24. Audio input and output test
25. LED lamp, calculators, music players and other application tools
26. 7.4V Lithium polymer battery ,5800mAh,after charging 7~8 hours ,working time lasts 10 hours

Specifications

Model	IPC-9800
Display	7 inch IPS TFT-LCD test monitor with capacitive touch screen ,1280*800 resolution
Network port	10/100M auto adapt,RJ45
IP discovery	auto-scan the whole network segment camera IP
Rapid ONVIF	search camera quickly, auto log in and display image from the camera, activate Hikvision camera
Hik test tool	activate Hikvision camera. Camera image test, support modify IP, user name and password etc parameters .
DH test tool	Dahua Camera image test, support modify IP, user name and password etc parameters
WIFI	Built in WIFI, speeds150M, display wireless camera image
IP camera type	Customized camera protocols welcome. ACTi,Dahua IPC-HFW2100P,Hikvision,DS-2CD864-E13,Samsung SNZ-5200、Tiandy TD-NC9200S2,Kodak IPC120L,Honeywell HICC-2300T, IPC,FSJ BY-1080Q,WEISKY IPC camera etc.
Video input/output	1 channel BNC input & 1 channel BNC looped output, NTSC/PAL (Auto adapt)
Video Level Test	Video signals measured in IRE or mV
Zoom Image	Support Analog camera and IP camera image zoom /move
Snapshot ,video record	Image Screen snapshot, record ,save ,view and record and play back
HDMI output	1 channel HDMI output,support 1920*1080P
12V/2Apower output	Output DC12V/2A power for camera
5V power output	5V 2A power output,as a Power bank
PoE power output	48V PoE power output,Max power 24W
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone
PTZ controller	RS485 control, Baud 600-115200bps,
Color bar generator	Output one channel PAL/NTSC color bar video signal for testing monitor or video cable.(red, green ,blue, white and black color)
UTP Cable tester	Test UTP cable connection status and display on the screen. Read the number on the screen
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal
Network test	IP address scan, link test, Ping test, Quickly search the connection IP camera and other device's IP address
PoE test	Measurement POE switch or PSE power supply voltage and cable connection status
POWER	
External power supply	DC 12V 2A

Battery	Built-in 7.4V Lithium polymer battery ,5800mAh
Rechargeable	After charging 7~8 hours, normal working time 10 hours
Parameter	
Operation setting	Capacitive touch screen, OSD menu, Chinese/English
Auto off	1-30 (mins)
General	
Working Temperature	-10°C----+50°C
Working Humidity	30%-90%
Dimension/Weight	231mm x 172mm x 52mm / 1.26Kg