



SXAD-SC-PC-OM3-D

PATCH CORDS, PIGTAILS, ADAPTERS

Fibre Optics Adapters

Insertion loss	0,1 dB ¹⁾
Operating temperature	-40 to +70 °C
Storage temperature	-40 to +70 °C
Life cycle	min. 1 000 insertions

1) Applies for ceramic inserts for LC, SC, ST, and E2000 adapters.

Solarix adapters are designed for easy mounting to various fibre optics patch panels and boxes. They feature high precision alignment sleeves for better reliability and reconnectability as well as ceramic inserts ensuring excellent and precise connections inside the adapter. The Solarix fibre optics adapters are colour coded according to their types (i.e. single mode or multimode). This colour resolution allows for quick and easy detection of the fibre used in the installation. E2000 adapters are supplied by R & M.

Singlemode	Type	Colour	Design
LC	APC	green	duplex
LC	UPC	blue	duplex/quadruplex
SC	APC	green	simplex/duplex
SC	UPC	blue	simplex/duplex
ST	UPC	-	simplex
E2000	APC	green	simplex/duplex

Multimode	Type	Colour	Design
LC OM2	UPC	grey	duplex
LC OM3	UPC	turquoise	duplex
SC OM2	UPC	grey	simplex/duplex
SC OM3	UPC	turquoise	simplex/duplex
ST OM2	UPC	-	simplex

Part No.	Description
SXAD-SC-PC-OS-D	SCPC SM Adapter OS Duplex
SXAD-SC-APC-OS-D	SCAPC SM Adapter OS Duplex
SXAD-SC-PC-OM2-D	SCPC MM Adapter OM2 Duplex
SXAD-SC-PC-OM3-D	SCPC MM Adapter OM3 Duplex