



SPECIFICATION

WWW.CANTONK.COM

"Reliable Digital Security Products Manufacturer"

Model NO.	IP100CW60H	IPCW60HJ130	KIP-130CW60H	IPCW60HE200	KIP-200CW60H	IPCW60HV200	IP200CW60SL	IPCW604XSL200	IP300CW60H	KIP-400CW60H	IPCW604XS400	KIP-400CW60A	KIP-500CW60H
Camera													
Image Sensor	OV9732	H65	IMX225	IMX323	IMX323	OV2718	IMX290	IMX290	IMX123	OV4689	OV4689	OV4689	IMX178
Main processor	HI3518EV200	HI3518EV200	HI3518EV200	HI3518EV200	HI3516CV200	HI3516CV200	Hi3516D	Hi3516D	Hi3516D	Hi3516D	Hi3516D	S2L55	Hi3516A
Resolution	720P	960P	960P	1080P	1080P	1080P	1080P	1080P	3MP	4MP	4MP	4MP	5MP
Effective Pixels	1280(H)*720(V)	1280(H)*960(V)	1305(H)*977(V))	1920(H)*1080(V)	1985(H)*1105(V)	1920(H)*1080(V)	1945(H)*1097(V)	1945(H)*1097(V)	2065(H)*1553(V)	2688(H)*1520(V)	2688(H)*1520(V)	2688(H)*1520(V)	2592(H)*1944(V)
Compression	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC												
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec												
S/N Ratio	≥52dB												
Scanning System	Progressive												
Video Output	Network												
Lens													
Focus Length	6mm	6mm	6mm	6mm	6mm	6mm	6mm	2.8-12mm	6mm	6mm	2.8-12mm	6mm	3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Motor	Fixed	Fixed	Motor	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Motor	Fixed	Fixed	Motor	Fixed	Fixed
Pixels	2M Pixels	2M Pixels	2M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	4M Pixels	4M Pixels	4M Pixels	6M Pixels
Night Vision													
Infrared LED	42μ x 4PCS												
Infrared Distance	40M												
IR Status	Under 10 Lux By CDS												
IR Power On	CDS Auto Control												
Network													
Ethernet	RJ-45 (10/100Base-T)												
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP												
ONVIF	Support ONVIF 2.4												
P2P	YES, Support QR Code												
POE	Optional, Support IEEE 802.3af												
WIFI	N/A												
Video Delay	0.3S (Within the Lan)												
Main Stream 1	1280*720@25fps	1280*960@25fps	1280*960@25fps	1920*1080@15fps	1920*1080@25fps	1920*1080@25fps	1920*1080@30fps	1920*1080@30fps	2048*1536@30fps	2560*1440@20fps	2560*1440@20fps	2560*1520@20fps	2592*1944@30fp
Main Stream 2	/	1280*720@25fps	/	/	/	/	/	/	1920*1080@30fps	2304*1296@30fps	2304*1296@30fps	2048*1520@20fps	2048*1520@30fp
Main Stream 3	/	/	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@30fps	1920*1080@20fps	1080@30fp
Sub Stream 1	720*480@25fps	720*480@25fps	720*480@25fps	720*480@15fps	720*480@25fps	720*480@25fps	720*480@30fps	720*480@30fps	720*480@30fps	720*480@20fps 720*480@30fps	720*480@20fps 720*480@30fps	720*480@20fps	720*480@30fps
Sub Stream 2	/	/	/	/	/	/	/	/	/	/	/	640*360@20fps	/
Sub Stream 3	/	/	/	/	/	/	/	/	/	/	/	/	/
Tri Stream	352*288@25fps	/	/	352*288@15fps	352*288@25fps	352*288@25fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@20fps 352*288@30fps	352*288@20fps 352*288@30fps	352*288@20fps	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari												
Smart Phone	iPhone, iPad, Android, Android Pad												
Camera Features													
Day/Night	Color/ B&W (IR-CUT)												
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)												
Corridor Pattern	/	/	/	/	/	/	Support	Support	Support	Support	Support	/	Support
Defog Mode	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	/	Support
ROI	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	/	Support
BLC	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	/	Support
HDR	/	/	/	/	/	/	/	/	Support	/	/	Support	/
WDR	Support												
Motion Detection	Support												
Privacy Masking	3 Rectangular Zone												
Recording Mode	NVR/NAS/CMS/Web												
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands												
General													
Housing	IP66												
Anti-cut Bracket	YES, Anti-Cut Bracket												
IR Cut Filter	YES												
Operation Temperature	-20℃ ~ +60℃ RH95% Max												
Storage Temperature	-20℃ ~ +60℃ RH95% Max												
Power Source	DC12V±10%, 1000mA												
Dimension	162(W) x 88(H) x 86(D)mm												
Weight	600g												

Guangzhou Cantonk Corporation Limited
 Add.: 1-5/F, Building 3, Jiayuan Industrial Park, Economic & Technological Development Zone, Luogang District, 510530 Guangzhou, China
 Tel. No.: +86 20 62355288 Fax No.: +86 20 62355211 Homepage: <http://www.cantonk.com> Email: info@cantonk.com